

Type	Output speed rpm		Torque range <sup>1)</sup>			Number of starts Max. [1/h]	Valve attachment <sup>2)</sup>			Handwheel		Weight <sup>3)</sup> approx. [kg]									
	50 Hz	60 Hz	Min. [Nm]	S2-15 min Max. [Nm]	S2-30 min Max. [Nm]		Standard EN ISO 5210	Option DIN 3210	Max. Ø steig. Spindel [mm]	Ø [mm]	Reduct. ratio										
SA 25.1	4 <sup>4)</sup>	4.8 <sup>4)</sup>	630	2,000	1,400	40	F25	G4	95	400	45 : 1	150									
	5.6 <sup>4)</sup>	6.7 <sup>4)</sup>									32 : 1										
	8	9.6									45 : 1										
	11	13									32 : 1										
	16	19									45 : 1										
	22	26									32 : 1										
	32	38									45 : 1										
	45	54									32 : 1										
	63	75									45 : 1										
	90	108									32 : 1										
SA 25.1	125	150	1,700	1,200	40	F25	G4	95	400	22.5 : 1	160										
	180	216	1,400	1,000						16 : 1											
	SA 30.1	4	4.8	1,250						4,000		2,800	40	F30	G5	115	500	44 : 1	190		
		5.6	6.7															33 : 1			
		8	9.6															44 : 1			
		11	13															33 : 1			
		16	19															44 : 1			
		22	26															33 : 1			
		32	38															44 : 1			
		45	54															33 : 1			
63		75	44 : 1																		
90		108	33 : 1																		
SA 30.1	125	150	3,200	2,200	40	F30	G5	115	500	33 : 1	260										
	180	216	2,800	2,000						22 : 1											
	SA 35.1	4	4.8	2,500						8,000		5,700	30	F35	G6	155	400	184 : 1	410		
		5.6	6.7															132 : 1			
		8	9.6															184 : 1			
		11	13															132 : 1			
		16	19															184 : 1			
		22	26															132 : 1			
		32	38															184 : 1			
		45	54															92 : 1			
63		75	66 : 1																		
90		108	46 : 1																		
SA 35.1	125	150	6,400	4,500	30	F35	G6	155	400	33 : 1	425										
	180	216	5,500	3,800						33 : 1											
	SA 40.1	4	4.8	5,000						16,000		11,200	20	F40	G7	175	500	184 : 1	510		
		5.6	6.7															128 : 1			
		8	9.6															184 : 1			
		11	13															128 : 1			
		16	19															184 : 1			
		22	26															128 : 1			
		32	38															14,000		9,800	184 : 1
		45	54															10,000		7,000	90 : 1
63		75	64 : 1																		
90		108	64 : 1																		
SA 40.1	4	4.8	5,000	16,000	11,200	20	F40	G7	175	500	180 : 1	750									
	5.6	6.7									132 : 1										
	8	9.6									180 : 1										
	11	13									132 : 1										
	16	19									180 : 1										
SA 48.1	4	4.8	10,000	32,000	22,400	20	F48	–	175	630	180 : 1										
	5.6	6.7									132 : 1										
	8	9.6									180 : 1										
	11	13									132 : 1										
	16	19									180 : 1										

**General information**

AUMA NORM multi-turn actuators require electric controls.

For sizes SA 25.1 – SA 48.1, AUMA offers AM or AC actuator controls. These can also easily be mounted to the actuator at a later date.

**Notes on table**

1) Torque range	The tripping torque is adjustable for directions OPEN and CLOSE within the indicated torque range.
2) Valve attachment	Indicated flange sizes apply for output drive types A and B1. Refer to separate dimension sheets for further output drive types.
3) Weight	Indicated weight includes AUMA NORM multi-turn actuator with 3-phase AC motor, electrical connection in standard version, output drive type B1 and handwheel.
4) Output speed	On request

Features and functions												
Type of duty	Standard: Short-time duty S2 - 15 min, classes A and B according to EN 15714-2											
	Option: Short-time duty S2 - 30 min, classes A and B according to EN 15714-2											
	For nominal voltage and +40 °C ambient temperature and at load with 35 % of the max. torque.											
Motors	3-phase AC asynchronous motor, type IM B9 according to IEC 60034-7, IC410 cooling procedure according to IEC 60034-6											
Mains voltage, mains frequency	Standard voltages:											
	<b>3-phase AC current</b> Voltages/frequencies											
	Volt	220	230	380	380	400	400	415	440	460	480	500
	Hz	60	50	50	60	50	60	50	60	60	60	50
	Special voltages:											
	<b>3-phase AC current</b> Voltages/frequencies											
Volt	220	440	525	575	600	660	690					
Hz	50	50	50	60	60	50	50					
	Further voltages on request											
	Permissible variation of mains voltage: ±10 %											
	Permissible variation of mains frequency: ±5 %											
Overvoltage category	Category III according to IEC 60364-4-443											
Insulation class	Standard: F, tropicalized											
	Option: H, tropicalized											
Motor protection	Standard: Thermostiches (NC)											
	Option: PTC thermistors (according to DIN 44082) PTC thermistors additionally require a suitable tripping device in the actuator controls.											
Self-locking	Self-locking: Output speeds up to 90 rpm (50Hz) or 108 rpm (60Hz) and from size SA 35.1 for output speeds up to 22 rpm (50Hz) or 26 (60Hz) NOT self-locking: SA 25.1 and SA 30.1 for output speeds from 125 rpm (50Hz) or 150 rpm (60Hz) and from size SA 35.1 for output speeds from 32 rpm (50Hz) or 38 (60Hz) Multi-turn actuators are self-locking if the valve position cannot be changed from standstill while torque acts upon the output drive.											
Motor heater (option)	Voltages: 110 – 120 V AC, 220 – 240 V AC or 380 – 480 V AC											
	Power depending on the size 12.5 – 25 W											
Manual operation	Manual drive for setting and emergency operation, handwheel does not rotate during electrical operation											
	Options:											
	Handwheel lockable Handwheel stem extension Power tool for emergency operation with square 30 mm or 50 mm											
Electrical connection	Controls: AUMA plug/socket connector with screw-type connection											
	Motor: Terminals within motor connection compartment											
	Options: Power connection via terminals or crimp type connection Gold-plated control plug (sockets and plugs)											
Threads for cable entries	Standard: Metric threads											
	Options: Pg-threads, NPT-threads, G-threads											
Terminal plan	TPA00R1AA-101-000 (basic version)											
Valve attachment	Standard: B1 according to EN ISO 5210											
	Options: A, B2, B3, B4, C, D according to EN ISO 5210 A, B, D, E according to DIN 3210 C according to DIN 3338											
	Special valve attachments: AF, AK, AG, B3D, ED, DD (IB1 or IB3 only for size 25.1, larger sizes upon request A prepared for permanent lubrication of stem											

## Technical data Multi-turn actuators for open-close duty with 3-phase AC motors

Electromechanical control unit	
Limit switching	Counter gear mechanism for end positions OPEN and CLOSED Turns per stroke: 2 to 500 (standard) or 2 to 5,000 (option)
	Standard: Single switch (1 NC and 1 NO) for each end position, not galvanically isolated
	Options: Tandem switch (2 NC and 2 NO) for each end position, switch galvanically isolated Triple switch (3 NC and 3 NO) for each end position, switch galvanically isolated Intermediate position switches (DUO limit switching), adjustable for each direction of operation
Torque switching	Torque switching adjustable for directions OPEN and CLOSE
	Standard: Single switch (1 NC and 1 NO) for each direction, not galvanically isolated
	Option: Tandem switch (2 NC and 2 NO) for each direction, switch galvanically isolated
Switch contact materials	Standard: Silver (Ag)
	Option: Gold (Au), recommended for low voltage actuator controls
Position feedback signal, analogue (options)	Potentiometer or 0/4 – 20 mA (electronic position transmitter)
Mechanical position indicator (option)	Continuous indication, adjustable indicator disc with symbols OPEN and CLOSED
Running indication	Blinker transmitter
Heater in switch compartment	Standard: Self-regulating PTC heater, 5 – 20 W, 110 – 250 V AC/DC
	Options: 24 – 48 V AC/DC or 380 – 400 V AC
	A resistance type heater of 5 W, 24 V AC is installed in the actuator in combination with AM or AC actuator controls.

Electronic control unit (option, only in combination with AC actuator controls)	
Non-Intrusive setting	MWG magnetic limit and torque transmitter Turns per stroke: 1 to 500 (standard) or 10 to 5,000 (option)
Position feedback signal	Via actuator controls
Torque feedback signal	Via actuator controls
Mechanical position indicator (option)	Continuous self-adjusting indication with symbols OPEN and CLOSED
Running indication	Blinking signal via actuator controls
Heater in switch compartment	Resistance type heater with 5 W, 24 V AC

Service conditions	
Use	Indoor and outdoor use permissible
Mounting position	Any position
Installation altitude	≤ 2,000 m above sea level > 2,000 m above sea level on request
Ambient temperature	Standard: –30 °C to +70 °C
	Options: –40 °C to +80 °C
	–50 °C to +60 °C
	–60 °C to +60 °C 0 °C to +120 °C
Humidity	Up to 100 % relative humidity across the entire permissible temperature range
Enclosure protection according to EN 60529	Standard: IP67 with AUMA 3-phase AC motor For special motors, differing enclosure protection is possible
	Options: <ul style="list-style-type: none"> <li>IP68 with AUMA 3-phase AC motor</li> <li>DS terminal compartment additionally sealed against interior of actuator (double sealed)</li> </ul>
	According to AUMA definition, enclosure protection IP68 meets the following requirements: <ul style="list-style-type: none"> <li>Depth of water: maximum 8 m head of water</li> <li>Duration of continuous immersion in water: Max. 96 hours</li> <li>Up to 10 operations during continuous immersion</li> </ul>

Pollution degree according to IEC 60664-1	Pollution degree 4 (when closed), pollution degree 2 (internal)		
Vibration resistance according to IEC 60068-2-6	2 g, 10 to 200 Hz (AUMA NORM), 1 g, 10 to 200 Hz (for actuators with AM or AC integral controls) Resistant to vibration during start-up or for failures of the plant. However, a fatigue strength may not be derived from this. Valid for multi-turn actuators in version AUMA NORM and in version with integral actuator controls, each with AUMA plug/socket connector. Not valid in combination with gearboxes.		
Corrosion protection	Standard:	KS	Suitable for use in areas with high salinity, almost permanent condensation, and high pollution.
	Options:	KX	Suitable for use in areas with extremely high salinity, permanent condensation, and high pollution.
		KX-G	Same as KX, however aluminium-free version (outer parts)
Coating	Double layer powder coating Two-component iron-mica combination		
Colour	Standard:	AUMA silver-grey (similar to RAL 7037)	
	Option:	Available colours on request	
Lifetime	AUMA multi-turn actuators meet or exceed the lifetime requirements of EN 15714-2. Detailed information can be provided on request.		

Further information	
EU Directives	Electromagnetic Compatibility (EMC): (2014/30/EU) Low Voltage Directive: (2014/35/EU) Machinery Directive: (2006/42/EC)
Reference documents	Brochure Electric actuators for industrial valve automation Dimensions SA 25.1 – SA 48.1/SAR 25.1 – SAR 30.1 Electrical data SA 25.1 – SA 48.1 with 3-phase AC motors Technical data for switches Technical data Electronic position transmitter/potentiometer Technical data Sizing of reduction gearings Technical data Manual forces at handwheel at multi-turn actuators SA 25.1 – 48.1, SAR 25.1 – 30.1, SAEx 25.1 – 40.1, SAREx 25.1 – 30.1